



**ecom-B**

- Sensor Options: O<sub>2</sub>, CO, NO
- Calculated NO<sub>x</sub>, CO<sub>2</sub>, Efficiency Excess Air
- CO Bypass Function
- IR Printer Option
- 7ft Sample Line, 9in Probe
- Pump Strength up to 1lpm
- Aluminum Housing



**ecom-B Plus**

- Sensor Options: O<sub>2</sub>, CO, NO
- Electronically Monitored Condensate Trap
- CO Bypass Function
- Integrated Printer
- 7ft or 9ft Sample Line, 9in or 12in Probe
- Enhanced Filtration
- Aluminum Housing




**ecom-CL 2**

- Sensor Options: O<sub>2</sub>, CO, NO
- Electronically Monitored Condensate Trap
- CO Bypass Function
- Integrated Printer
- 7ft Sample Line, 9in Probe
- Enhanced Filtration
- All-in One Unit – Aluminum Case and Analyzer



**ecom-D**

- Sensor Options: O<sub>2</sub>, CO, NO, NO<sub>2</sub>, SO<sub>2</sub>, C<sub>x</sub>H<sub>y</sub>, H<sub>2</sub>S, CO<sub>2</sub> & CH<sub>4</sub> IR
- Electronically Monitored Condensate Trap
- Peltier Cooler Option
- IR Printer Option
- WIFI and free App
- 9ft or 15ft Sample Line, 12in Probe
- Aluminum Case
- Pump Strength up to 1lpm



**ecom-EN2-Series (compliance level analyzer)**

- Sensor Options: O<sub>2</sub>, CO, NO, NO<sub>2</sub>, SO<sub>2</sub>, C<sub>x</sub>H<sub>y</sub>, H<sub>2</sub>S, CO<sub>2</sub> & CH<sub>4</sub> IR
- Automated Moisture Removal
- Peltier Cooler
- Advanced Filtration
- Onboard Printer
- WIFI and free App, Optional Compliance SW
- Bluetooth Option
- Pump Strength up to 2.2lpm
- 15ft Sample Line, 12in Probe



**ecom-J2KN Series (compliance level analyzer)**

- Sensor Options: O<sub>2</sub>, CO, NO, NO<sub>2</sub>, SO<sub>2</sub>, C<sub>x</sub>H<sub>y</sub>, H<sub>2</sub>S, CO<sub>2</sub> & CH<sub>4</sub> IR
- Automated Moisture Removal
- Industrial Cooling & Filtration
- Handheld Control Unit
- Onboard Printer
- WIFI or Bluetooth Option
- Optional Fresh Air Purge Valve
- Pump Strength up to 2.6lpm
- 15ft Sample Line, 12in Probe



**ecom-J2KNpro TECH (compliance level analyzer)**

- Can be equipped with NDIR, PAS, Chemiluminescence & EC Sensors
- Automated Moisture Removal
- Industrial Cooling & Filtration
- Handheld Control Unit
- Onboard Printer
- WIFI or Bluetooth Option
- Fresh Air Purge Valve
- Pump Strength up to 2.6lpm
- 15ft Sample Line, 12in Probe



**ecom-Software Options**

- For D6522 & SQMD Compliance Testing
- Generation of Snapshot Report
- MS Operating System Based
- Free App for Single Snapshot and Remote Display (iOS and Android)
- Transferable Customer & Equipment Database
- SD Card Upload Function



**ecom-Manometers (differential pressure meters)**

- ecom-UNO:  
Range +/- 0.8 iwg  
Resolution 4.02 iwg  
Over Range +/- 1.2 iwg
- ecom-DP (single or dual channel):  
Range Opt. +/- 0 to 6.02 iwg, +/- 0 to 4,014 iwg  
Accuracy +/- 3% of Measured Value



**ecom-LS Series (leak detection)**

- ecom-LSG - Gas Leak Detector  
Optical and Acoustical Warning  
Flex Arm
- ecom-LSK - Coolant Leak Detector  
Optical and Acoustical Warning  
Flex Arm